


Flush pressure transmitter

PM-025-RES30-E-ZVG/US /P



- 1 Aseptoflex sealing edge
2 Aseptoflex thread

EC 1935/2004 EHEDG Certified FCM

Application

Application	hygienic systems		
Media	viscous media and liquids with suspended particles; liquids and gases		
Medium temperature [°C]	-25...125; (145 max. 1h)		
Pressure rating	100 bar	1450 psi	10 MPa
Min. bursting pressure	350 bar	5070 psi	35 MPa
Type of pressure	relative pressure		
no dead space	yes		

Electrical data

Operating voltage [V]	14...30 DC		
Min. insulation resistance [$M\Omega$]	100; (500 V DC)		
Protection class	III		
Reverse polarity protection	yes		

Inputs / outputs

Number of inputs and outputs	Number of analog outputs: 1
------------------------------	-----------------------------

PM2053



Flush pressure transmitter

PM-025-RES30-E-ZVG/US/ /P


Outputs			
Total number of outputs		1	
Output signal		analog signal	
Number of analog outputs		1	
Analog current output [mA]		4...20	
Max. load [Ω]		550; ($U_b = 24 \text{ V}$; $(U_b - 13 \text{ V}) / 20 \text{ mA}$)	
Overload protection		yes	
Measuring/setting range			
Measuring range	-1...25 bar	-15...363 psi	-0.1...2.5 MPa
Analog start point	-1...18.8 bar	-15...272 psi	-0.1...1.88 MPa
Analog end point	5.3...25 bar	76...363 psi	0.53...2.5 MPa
in steps of	0.1 bar	1 psi	0.01 MPa
Factory setting		ASP = 0.0 bar	AEP = 25.0 bar
Accuracy / deviations			
Repeatability [% of the span]		< ± 0,1; (with temperature fluctuations < 10 K; Turn down 1:1)	
Characteristics deviation [% of the span]		< ± 0,6; (Turn down 1:1 linearity, incl. hysteresis and repeatability limit value setting to DIN 16086)	
Linearity deviation [% of the span]		< ± 0,5; (Turn down 1:1)	
Hysteresis deviation [% of the span]		< ± 0,1; (Turn down 1:1)	
Long-term stability [% of the span]		< ± 0,1; (Turn down 1:1; per year)	
Temperature coefficient zero point [% of the span / 10 K]		< ± 0,1; (0...80 °C)	
Temperature coefficient span [% of the span / 10 K]		< ± 0,2; (0...80 °C)	
Reaction times			
Max. response time analog output [ms]		3	
Software / programming			
Parameter setting options		Zero point; span	
Interfaces			
Communication interface		EPS	
Operating conditions			
Ambient temperature [°C]		-25...80	
Storage temperature [°C]		-40...100	
Protection		IP 67	

PM2053



Flush pressure transmitter

PM-025-RES30-E-ZVG/US/ /P

Tests / approvals				
EMC	EN 61000-4-2 ESD	4 kV CD / 8 kV AD		
	EN 61000-4-3 HF radiated	10 V/m		
	EN 61000-4-4 Burst	2 kV		
	EN 61000-4-6 HF conducted	10 V		
Shock resistance	DIN IEC 68-2-27	50 g (11 ms)		
Vibration resistance	DIN IEC 68-2-6	20 g (10...2000 Hz)		
MTTF [years]		271		
Mechanical data				
Weight [g]		474		
Material	stainless steel (1.4404 / 316L); PEI; FKM			
Materials (wetted parts)	ceramics (99.9 % Al2O3); PTFE; stainless steel (1.4404 / 316L); surface characteristics: Ra < 0,4 / Rz 4			
Min. pressure cycles	100 million			
Process connection	threaded connection Aseptoflex external thread Aseptoflex			
Remarks				
Remarks	The 3-A qualification is only valid if adapters with 3-A qualification are used for installation.			
Pack quantity	1 pcs.			
Electrical connection				
Connector: 1 x M12; Contacts: gold-plated				
				

Connection

