

WL12G-N530





Ordering information

Туре	Part no.
WL12G-N530	1016309

Other models and accessories -> www.sick.com/

Illustration may differ



Detailed technical data

Features

Sensor/ detection principle	Photoelectric retro-reflective sensor
Dimensions (W x H x D)	15 mm x 49 mm x 41.5 mm
Housing design (light emission)	Rectangular
Sensing range max.	0 m 3 m ¹⁾
Sensing range	0 m 2.7 m ¹⁾
Type of light	Visible red light
Light source	LED
Adjustment	Potentiometer

¹⁾ Reflector PL80A.

Mechanics/electronics

Supply voltage	10 V DC 30 V DC
Ripple	\leq 5 V _{pp}
Power consumption	65 mA ¹⁾
Switching output	NPN
Switching mode	Light switching
Response time	$\leq 0.5 \text{ ms}^{-2}$
Connection type	Male connector M12, 5-pin
Housing material	Metal, Zinc diecast Metal, Zinc diecast

¹⁾ Without load.


 $^{\rm 2)}$ Signal transit time with resistive load.

Optics material	Plastic, PMMA	
Enclosure rating	IP67	
Ambient operating temperature	-25 °C +60 °C	
Ambient storage temperature	-40 °C +75 °C	
UL File No.	NRKH.E181493 & NRKH7.E181493	

¹⁾ Without load.

²⁾ Signal transit time with resistive load.


Adjustments possible




Standard direction of the material being detected
Mounting hole, Ø 4.2 mm

Connection diagram


Cd-146



Characteristic curve




Sensing range diagram



Re	flector type	Operating range
1	PL 80 A	0 2.7 m
2	PL 40 A	0 1.6 m
3	PL 30 A	0 1.3 m
4	PL 20 A	0 1.0 m

Dimensional drawing (Dimensions in mm (inch))



- ① LED signal strength indicator
- Center of optical axis
- ③ M4 threaded mounting hole 4 mm deep
- ④ Mounting hole, Ø 4.2 mm
- ⑤ Function selector

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com



Online data sheet

